



# Combine Grain Tank Extensions

For various John Deere, Case IH and New Holland Combines.



## FEATURES:

- ❑ Minimal hardware required for Quick and Easy Assembly
- ❑ Snap-ring Extensions allow you to set up and fold down in seconds.
- ❑ Four Inspection Windows - One at each corner for increased visibility.
- ❑ Heavy Duty 14 gauge extensions with formed tube and angle iron frames provide maximum strength and stability.
- ❑ State-of-the-art Laser Cut panels for precision fit and finish.
- ❑ Powder-coat paint system for a durable, high quality finish.



# Combine Grain Tank Extensions

For various John Deere, Case IH and New Holland Combines.



## SPECIFICATIONS:

The information below is general in nature and not intended for specific application purposes. J&M Mfg Co., Inc. reserves the right to make changes in product, specifications or pricing without notice or obligation.

Model	EXTENSION HEIGHTS			ADDED BUSHEL CAPACITY PER EXTENSION*		
	A Size	B Height Above Cab	Height above cab roof with Bin Extension Folded	Standard	Added	Total
<b>Case IH Series</b>						
Case IH 1660, 2166-2366	Regular	+15"	---	185 bu.	105 bu.	290 bu.
Case IH 1660, 2166-2366	Large	+23"	+2"	185 bu.	150 bu.	335 bu.
Case IH 1680, 2188-2388, 2377, 2577	Regular	+17"	+4"	210 bu.	95 bu.	305 bu.
Case IH 1680, 2188-2388, 2377, 2577	Large	+25"	+4"	210 bu.	140 bu.	350 bu.
Case IH AFX 8010, 7010	Regular	+18"	+3"	330 bu.	35 bu.	365 bu.
Case IH AFX 8010, 7010	Large	+26"	+3"	330 bu.	105 bu.	435 bu.
<b>New Holland Series</b>						
NH TR89-99	Regular	+17"	+3"	240 bu.	100 bu.	340 bu.
NH TR89-99	Large	+25"	+3"	240 bu.	145 bu.	385 bu.
NH CR 920	Regular	+18"	+3"	205 bu.	110 bu.	315 bu.
NH CR 920	Large	+26"	+3"	205 bu.	180 bu.	385 bu.
NH CR 940	Regular	+18"	+3"	255 bu.	110 bu.	365 bu.
NH CR 940	Large	+26"	+3"	255 bu.	180 bu.	435 bu.
NH CR 960	Regular	+18"	+3"	300 bu.	65 bu.	365 bu.
NH CR 960	Large	+26"	+3"	300 bu.	135 bu.	435 bu.
<b>John Deere Walker Series</b>						
JD 9400-9410-9450	Regular	+17"	+3"	182 bu.	125 bu.	307 bu.
JD 9400-9410-9450	Large	+25"	+3"	182 bu.	170 bu.	352 bu.
JD 9500-9510-9550	Regular	+17"	+3"	202 bu.	105 bu.	307 bu.
JD 9500-9510-9550	Large	+25"	+3"	204 bu.	150 bu.	354 bu.
JD 9600-9610-9650	Regular	+17"	+3"	240 bu.	110 bu.	350 bu.
JD 9600-9610-9650	Large	+25"	+3"	240 bu.	160 bu.	400 bu.
<b>John Deere STS Series</b>						
JD STS 9660	Regular	+15"	+2"	250 bu.	100 bu.	350 bu.
JD STS 9660	Large	+23"	+2"	250 bu.	150 bu.	400 bu.
JD STS 9750	Regular	+15"	+2"	300 bu.	50 bu.	350 bu.
JD STS 9750	Large	+23"	+2"	300 bu.	100 bu.	400 bu.
JD STS 9760	Regular	+15"	+2"	300 bu.	50 bu.	350 bu.
JD STS 9760	Large	+23"	+2"	300 bu.	100 bu.	400 bu.
JD STS 9770	Regular	+15"	+2"	300 bu.	50 bu.	350 bu.
JD STS 9770	Large	+23"	+2"	300 bu.	100 bu.	400 bu.
JD STS 9860	Regular	+15"	+2"	300 bu.	50 bu.	350 bu.
JD STS 9860	Large	+23"	+2"	300 bu.	100 bu.	400 bu.



Model	EXTENSION HEIGHTS			ADDED BUSHEL CAPACITY PER EXTENSION*		
	A Size	B Height Above Cab	Height above cab roof with Bin Extension Folded	Standard	Added	Total
<b>John Deere STS 60 &amp; 70 Series</b>						
JD STS 60 & 70 Series	Regular	+10"	+2"	250-300 bu.	80 bu.	330/380 bu.
JD STS 60 & 70 Series	Large	+16"	+2"	300 bu.	130 bu.	430 bu.
<b>Note: Tip up kits are constructed of heavy duty 12 gauge steel panels and are <u>NOT</u> to be installed on 60 or 70 Series combines that feature original factory molded plastic corners.</b>						



**J. & M. Mfg. Co., Inc.**

P.O. Box 547 Ft. Recovery, OH 45846

Ph: (419) 375-2376 Fax: (419) 375-2708

[www.jm-inc.com](http://www.jm-inc.com)

© Registered Trademark of J. & M. Mfg., Co. Inc.

## GUARANTEE

J. & M. MANUFACTURING CO., INC. guarantees against any faulty construction or materials for a period of **ONE** year.

We reserve the right to inspect and decide whether material or construction was faulty or whether abuse or accident voids our guarantee.

Specifications are subject to change without notice or obligation. ☞